

## **TOPMIX<sup>®</sup>**

### **FLOOR SURFACE HARDENER**

**TOPMIX<sup>®</sup>** is a pre-blended cementitious powder mixture, containing selected nonmetallic aggregates, special cements and compatible admixtures.

**TOPMIX<sup>®</sup>** is used to create durable topping of monolithic concrete floors. Immediately after usual pouring of the concrete slab **TOPMIX<sup>®</sup>** is sprinkled on the fresh wet concrete. Repeated power trowelling forms durable, smooth and non-slip surface.

**TOPMIX<sup>®</sup>** topping provides increased resistance to the penetration of oil and grease. Industrial floors with **TOPMIX<sup>®</sup>** dry shake topping are extensively used in warehouses, factories, workshops, shopping centres etc. and generally everywhere, where durable and abrasion resistant surface is required.

#### **SPECIAL PROPERTIES**

- ◆ Resistance to medium duty.
- ◆ Dust free.
- ◆ Cost effective.
- ◆ Guaranteed quality – no site production.

#### **TECHNICAL DATA**

- ◆ Abrasion resistance:  $\leq 6,0$   $\text{cm}^3 / 50 \text{cm}^2$  MSZ EN 13892-2:2003 Class: A6
- ◆ Compressive strength:  $\geq 80$   $\text{N/mm}^2$  MSZ EN 13892-2:2003 Class: C80
- ◆ Bending-tensile strength:  $\geq 7,0$   $\text{N/mm}^2$  MSZ EN 13892-2:2003 Class: F7
- ◆ Temperature for use: 5°C-30°C

#### **PACKAGING**

- ◆ **TOPMIX<sup>®</sup>** is supplied in 30 kg bags, 40 bags on a pallet, total: 1200 kg.
- ◆ **TOPMIX<sup>®</sup>** is supplied in natural grey colour. Possible other colours to be consulted.

#### **SHELF LIFE**

12 months from the dispatching date in original unopened packs. Protect from frost and wet conditions.

#### **SAFETY AND HEALTH PROTECTION**

The product contains cement, therefore it is necessary to wear protective gloves and goggles.

**TOPMIX<sup>®</sup>**